

VESTA outdoor curtain PIRCAM

ANTIMASKING   PET IMMUNITY   GRADE 2

- PIRCAM wireless curtain detector VESTA for outdoor use
- Coverage of 12 meters, 8°(V) / 90°(H)
- Camera: 640x480@3ips, 320x240@3/6ips
- 102° optics, IR illumination of 7 meters
- Antimasking and antipet function 60 kg
- Includes VESTA-213 swivel mount
- Grade 2.



Reference / Model	VESTA-210 / VST-892-EXC-IL
specs	

## VESTA outdoor curtain PIRCAM

**Reference / Model****VESTA-210 / VST-892-EXC-IL**

Detects motion using PIR technology with curtain detection pattern  
Vertical/horizontal curtain detection pattern  
Change the detection pattern by changing the direction of the PIR lens  
Horizontal detection pattern provides anti-pets up to 60kg / 75cm  
Advanced dynamic rate adjustment algorithms to maintain image transfer rate based on signal quality  
Three alarm image processing options: 3 photos at 640x480, 3/6 photos at 320x240 or 1 photo at 320x240  
Image delivery on demand  
Night illumination capacity by means of infrared light, up to 7 meters of range  
Anti-masking function  
F1 technology speeds up the signal transmission speed and increases the communication range  
LED status indicator  
Periodic monitoring signals ensure proper operation  
Compatible with Climax F1 gateways/control panels and the VESTA-030 repeater (RP-29-F1)  
tamper protection  
Low battery detection  
Ideal for balconies, pools, garages, driveways, French doors, sidewalks, etc. Includes swivel mount  
RF frequency: 868MHz  
Communication range of 400 ~ 900 meters in open field  
10k, 20k, 30k, 50k, 80k data rate  
Vertical detection range: 12 meters, 8°, installed at a height of 1.4 ~ 2.5 meters  
Horizontal detection range: 12 meters, 90°, installed at a height of 1.4 meters  
VGA-CMOS sensor  
Horizontal viewing angle: 102°  
Resolution: 640x480, 320x240  
Infrared lighting up to 7 meters  
Power: 4 lithium batteries L91 1.5V  
Battery life of up to 8 years  
Operating temperature -10°C ~ +45°C  
Relative humidity up to 85% (non-condensing)  
Swivel Angles (with included swivel mount): 30° vertical  
Degree of protection IP65  
Dimensions (without stand): 73 (W) x 165.4 (H) x 86 mm  
EN50131 Grade 2 Certificate