

## VESTA-243

ESGW-F1-ZW-Battery



### VESTA EasySmart Gateway



- VESTA EasySmart radio security center with advanced home automation functions
- Up to 160 devices
- 2 security areas
- Includes F1 868Mhz radio receiver, Z-Wave Plus receiver, and IP module
- Event and photo report via APP (MANITOU, encrypted MANITOU, CID, SIA, FTP, HTTP)
- Push notification via a cloud server
- Free App
- Supports indoor and outdoor PIRCAMS
- Supports DAHUA IP cameras
- Programming of up to 100 automation rules
- Compatible with Z-Wave devices from other manufacturers
- Three different arming modes
- Remote management of lights, thermostats, locks, appliances via a smartphone app and PC web browser
- Firmware upgrade capability



#### Reference / Model

**VESTA-243 / ESGW-F1-ZW-Battery**

Radio security central with advanced home automation functions

Allows up to 160 devices

2 security areas

Incorporates F1 868Mhz radio receiver

Built-in Z-Wave Plus receiver

Built-in IP module

Event and photo reporting via APP (MANITOU, encrypted MANITOU, CID, SIA, FTP, HTTP)

Free APP for User/Installer

Full programming from the WEB platform/ APP installer "SmartHomeSec" in less than 10 minutes

Compatibility with the large catalogue of more than 50 F1 devices: keypads, sirens, smoke sensors, PIR detectors, PIRCAMS, temperature sensors, door contacts, perimeter detectors, vibration sensors, etc.

Supports indoor and outdoor PIRCAMS ( User can make photo requests from the APP)

Programming of up to 100 automationrules (e.g. automatic watering, presence simulation, control of any device by calendars, auto-arming).

## VESTA-243

ESGW-F1-ZW-Battery



## VESTA EasySmart Gateway

Reference / Model	VESTA-243 / ESGW-F1-ZW-Battery
	Compatible with Z-Wave devices from other manufacturers
	Allows WiFi connectivity by using WIFI dongle VESTA-064N
	Supports DAHUA IP cameras
	Logging of up to 500 events
	Remote firmware upgrade
	Power supply: 100V ~ 240V AC, 50/60Hz (5V DC /1A adapter included)
	Built-in battery backup with up to 10 hours of battery life
	Operating temperature of -10°C ~ +45°C
	Relative humidity up to 85% (non-condensing)
	Dimensions: 114 x 77 x 33 mm